


Mega-Rib Panel

Product Data



MEGA-RIB PROFILE

Applications

Exposed fastener wall/roof panel used on slopes down to 1:12. Tape sealant is required on seam (side-laps). Standard panel lengths up to 40'. Please inquire for longer lengths.

Substrates

Plywood or Purlins.

Material

- Standard - 24 GA. Steel ASTM A792 (50 ksi) AZ55 - Bare
AZ50 - Painted
- Optional - 22 GA. Steel ASTM A792 (50 ksi) AZ55 - Bare
AZ50 - Painted
- 26 GA. Steel ASTM A792 (80 ksi) (Narrow Coverage) AZ50 - Bare
AZ50 - Painted
- 26 GA. Steel ASTM A792 (80 ksi) (Full Coverage) AZ50 - Bare
AZ50 - Painted
- **Adelanto Only**
- 18 GA. and 20 GA. Steel ASTM A792 (50 ksi) AZ50 - Painted
(limited availability)

NOTE:

All data represented on this sheet may not be applicable to all widths and gauges. Please contact McElroy Metal for more information.

Manufacturing

Roll formed in factory.

Finishes


Acrylic Coated Galvalume®
Fluoropolymer (Kynar 500® PVDF resin-based)
Siliconized Polyester and Polyester

Pan Conditions


Oil canning is inherent in all metal panels and is not cause for panel rejection.

Testing *

- Uplift: UL 580 Class 90, ASTM E1592
- Air & Water Infiltration: E1646 and E1680
- Impact Resistance: UL 2218 Class 4
- Fire Resistance: UL 263 & UL 790 Class A
- Florida Product Approval: FL 1832.8 (non-structural)
FL 1747.6 (structural)
- Miami Dade Approval: NOA# 20-1215.10
- *Testing and Approvals are product specific. Please inquire for details.*



FOAM INSIDE CLOSURE



FOAM OUTSIDE CLOSURE

